

Bekafix® Ultra Posts

A higher rigidity profiled post, for medium to high security applications, at an excellent price-quality ratio.



Product detail



Compatible products

- All Nylofor panels (in superposition) up to 4 m
- CreaZen panels
- Securifor panels up to 3 m

Benefits

With the Bekafix Ultra post, all the benefits of the standard Bekafix post are kept, but by increasing the inertia considerably, its application range has become much wider.

- Quick installation.
- Concrete plates maintained directly in between the posts, without any plate holders.
- Same accessories as the standard Bekafix posts, except for metallic fixators.
- 10 Years guaranty in extreme conditions

Profile

- Tubular post, profiled in "H" shape, cross section of the post: 70 x 44 mm, plate thickness: 1.75 mm
- With central holes every 15 cm, for fixing of the special metal security clips with bolts
- With side punched holes for positioning and fixing of the panels by means of fixing clips
- **I/V:** 7.29 cm³ | **Yield strength:** 550 MPa | **Relative strength Bekafix Ultra:** 401 compared to 132 for Bekafix posts
- Post cap with hook to hang panels for ease of installation.

Accessories same as Bekafix Standard post, except for metallic fixators

- Fixing system: plastic coated metal clip with, as an option, one-way security bolt
- Bekafix installation plier
- Spider fixing for installation of Securifor panels
- Base plate for installation on tiles or concrete floor
- Connection piece to create bent arm for panels or extension
- Single or double bent arms for Bekafix range

Coating technique

Magnelis®: inside and outside and polyester coated (minimum 60 microns).

Colors

Green RAL 6005, Black RAL 9005, Anthracite RAL 7016 and White RAL 9010

Other colors are available on request.

BEKAFIX® ULTRA POSTS			
Fence height mm	Post length (mm)	Number of fixators per intermediate post	Number of fixators per end post
1230 / 1330*	1775	6	3
1430 / 1530*	1975	6	3
1630 / 1730*	2175	6	3
1930*	2475	8	4
2030	2575	8	4
2430	3175	8	4
3000	3775	10	5
4000	4775	12	6

* The same post can be used for installation in concrete or footplate
Other heights available on request

Europe: Blokkestraat 34b,
B-8550 Zwevegem
Tel: B: +32 56 73 46 46

USA: 3309 SW Interstate 45,
Ennis, TX 75119
Tel: +1 972 878 7000

Middle East: P.O. Box 293517 DAFZA,
Building E 5, Block A 8th Floor, Office 802
Tel: +971 04 6091122

Africa: B10, Bergriver Business Park,
Paarl, 7646
Tel: +27 021 868 7300